



## Furniture Oil

solvent-free

150 ml - 375 ml - 1 l - 2,5 l - 10 l



As a primer and final coat, as well as for the care of furniture, interior fittings and toys. For absorbent surfaces made of wood.

- Crystal Clear Ingredient Declaration ([www.biofa.de](http://www.biofa.de))
- Low emission
- Made from natural raw materials
- 98% renewable and mineral ingredients
- Colorless
- Breathable and antistatic
- Dirt and water repellent
- Meets DIN 53160 (fastness to perspiration and saliva) and QNG-Ready




### Properties:

BIOFA furniture oil is a special boiling and mixture of natural oils, resins, bee, carnauba and rice husk wax. The oil has a greenish colour due to its high hemp oil content in the container, but this is no longer visible on the dried wood surface. It is suitable for all wooden surfaces in furniture and interior design. The oil penetrates well into the wood, revitalises and deepens the natural structure and tone of the treated wood and creates diffusible, resistant and antistatic surfaces.

### Ingredients:

Linseed oil, hemp oil, wood oil, soya oil, ricinseed oil-colophony resin, rice husk wax, beeswax, carnauba wax, matting agent, hydrophobing agent, defoamer, cobalt polymer drier, calcium and manganese drier, antioxidant.



### Processing steps:

- 1. Preparation** Substrate must be dry (wood moisture content below 12%) and free of dirt and old paint coats. Finish sanding with 150 - 180 grit is recommended.
- 2. Base coat** Remove any protective skin that may have formed; mix thoroughly. Apply with brush, lint-free rag, or sprayer. Polish to sheen with white pad or cloth after 30-50 minutes.
- 3. Topcoat** A second coat after 6-12 hours will improve the finish quality.
- 4. Equipment cleaning** Immediately after use, clean with BIOFA Brush Cleaner 0600 (solvent-free) or BIOFA Thinner 0500.
- 5. Care** When required apply a small amount of furniture oil on a soft, lint-free rag, and apply an even, very thin coat. Then polish out the finish.



## Important:

**Be sure to test product before proceeding! Ensure sufficient fresh air circulation when processing and drying! Do not use below 16°C!**

## Recommended Equipment:



- 1. 009949 / 009934** Flat brush, professional quality 50 mm / 70 mm for oily-based products
- 2. 009951 / 009980** Varnish roller microfiber 100 mm / 180 mm
- 3. 009952 / 009996** Roller bracket 100 mm / 180 mm rollers
- 4. 009963 / 009925** Pad green grit 180 Ø 150mm / pad brown Ø 150mm with adhesive fleece for use by hand or with a polishing machine
- 5. 009974 / 009984** Pad white Ø 150mm / pad white with adhesive fleece Ø 150mm for buffing
- 6. 0600** BIOFA Brush Cleaner for cleaning the working equipment

## Drying:

Dry and ready for overcoating after approx. 6-12 hrs. (20°C/ 50-55 % rel. humidity).  
Fully cured and ready for unrestricted use after 7-10 days.

## Consumption/yield per coat:

20-30 ml/m<sup>2</sup> or 35-50 m<sup>2</sup>/l, depending on absorption of the surface.

## Storage:

Keep cool, dry and properly sealed. May form skin. Remove skin before next use. Screen oil as needed!

## Container:

Glass bottle 150 ml  
Coated metal containers 375 ml, 1 l, 2,5 l, 10 l

## Disposal:

Deposit liquid product leftovers at collection point for old paints/ old varnishes, and/or dis-pose in compliance with local statutory regulations. Minor leftovers and soaked processing materials can be disposed in the household waste after drying out. Only recycle fully emptied and cleaned containers. Not completely emptied and cleaned containers must be treated and disposed like the product!

AVV waste code according to European waste list: 08 01 12

## Hazard and safety information:

**Store work materials and clothing soaked with product in an airtight metal container or soak in water and spread out on a non-flammable surface to dry - (risk of spontaneous combustion!) The product itself is not self-igniting.**  
**Keep out of the reach of children. If medical advice is required, have packaging or labelling ready. Do not get in eyes, on skin or on clothing. In case of contact with skin, wash with plenty of soap and water. Ensure adequate skin protection! When spraying, do not inhale the spray mist and wear suitable respiratory protection (combination filter A2/P2) and safety goggles. Use respiratory protection (dust filter P2) when sanding. Do not allow to enter the sewage system, waterways or soil. A typical odour of the natural raw materials is possible.**

**Safety data sheet available on request**

---

**2049 contains max. 1 g/l VOC.**

---